

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Cancelled)

1 2. (Currently Amended) The club organizer of claim [1] 9 wherein
2 the grooves are formed so as to suit both left and right handed clubs.

1 3. (Currently Amended) The club organizer of claim [1] 9 and
2 including a collar means supported along the rim and upon which is supported the
3 cover means.

1 4. (Currently Amended) The club organizer of claim [1] 9 and
2 including tubular partitioning means extending downwardly from respective ones of
3 the apertures for passing the shaft of each of the iron clubs therethrough.

Claims 5-7 (Cancelled)

1 8. (Currently Amended) The club organizer of claim [5] 9 wherein
2 the arcuately shaped ridge member is inclined so as to have an upper end and a
3 lower end with each of the apertures being at a different height to each other of the
4 apertures, whereby the head of each of the iron clubs are vertically spaced apart
5 from each other.

1 9. (New) A club organizer for a golf club carry bag, comprising a cover
2 means adapted to fit across the opening of the golf club carry bag, the cover means
3 having an arcuately shaped ridge member adapted to be supported along a portion
4 of a rim defining the opening of the carry bag, the ridge member having a convex
5 outer side wall and a concave inner side wall defining a concavity, the ridge
6 member having an uppermost planar surface between the convex outer side wall
7 and the concave inner side wall, and web means located within the concavity for
8 rigidizing the ridge member by urging the ridge member against the rim, the ridge
9 member being so inclined as to have an upper and lower end and including a
10 plurality of descending apertures for passing the shaft of each of the iron clubs
11 therethrough and into the carry bag, each of the apertures including a groove formed
12 through the outer side wall for locating the head of respective ones of the iron clubs
13 so that, in accordance with the indication of the ridge member, each of the apertures
14 is at a different height to each other of the apertures whereby the head of each of
15 the iron clubs are vertically spaced apart from each other and are directed away
16 from the concavity, and the web means defining a plurality of apertures for locating
17 the head of each of the wood clubs, the uppermost planar surface of the ridge
18 member extending between the upper end and lower end and sloping downwardly
19 towards the concavity from the convex outer side wall to the concave inner side wall.